

FLESSIBILI DOCCIA ESTRAIBILE

PULL-OUT FLEXIBLE HOSES






DATI TECNICI - TECHNICAL DATA:

I flessibili estraibili made in Italy sono trecciati e raccordati per il miglior confort in cucina o nelle altre possibili installazioni. La gamma varia dai trecciati in acciaio inox o in nylon colorato fino agli inox ricoperti in pvc. Tutti i flessibili estraibili sono dotati di maschio girevole e attacco girevole antitorsione, per una maggiore praticità d'uso.

The pull-out Made in Italy hoses are braided and connected for the best comfort in the kitchen or in the other possible installations. The range varies from stainless steel, or colored nylon, braided hoses up to the stainless steel hoses covered in pvc. All the pull-out flexible hoses are equipped with a swivelling male and a swivelling anti-torsion connection, for the most practical use.

CARATTERISTICHE - FEATURES:

	PRESSIONE D'ESERCIZIO OPERATING PRESSURE 	TEMPERATURA D'IMPIEGO WORKING TEMPERATURE 	FORO MINIMO PASSAGGIO D'ACQUA FITTING INNER DIAMETER 	RAGGIO CURVATURA MINIMO MINIMUM BENDING RADIUS 
Tubo Dn8	10 BAR	-10°C - +90°C	6 mm	30 mm

MATERIALI - MATERIALS

TUBO HOSE		Treccia in NYLON - Tubo interno: gomma EPDM atossico NYLONB raid - Internal pipe: EPDM rubber, atoxic.	
		Treccia Inox AISI 304 - Tubo interno: gomma EPDM atossico Braid Stainless AISI 304 - Internal pipe: EPDM rubber, atoxic.	
		Treccia in Acciaio Inox AISI 304 ricoperto in PVC colorato Tubo interno: gomma EPDM atossico Braid stainless steel AISI 304 coated with colored PVC Internal pipe: EPDM rubber, atoxic.	
RACCORDI FITTINGS		CW614N CW617N	Ottone CW614N e CW617N nichelato o cromato Brass CW614N and CW617N nickel plated or chrome plated
BUSSOLE SLEEVES		Ø 12 mm	Acciaio Inox AISI 304 - Stainless steel AISI 304